

MODEL 97



Special calender for pieces or continuous fabrics, used for :

- Transfer printing
- Direct inks reactivation
- Thermosetting - heatsetting

Versatile and polyvalent calender, developed for transfer printing of all the follows work conditions, according to required options:

- Printing paper in roll and material to be printed in roll
- Printing paper in roll and material to be printed in pieces
- Printing paper in sheets and material to be printed in pieces

1. Characteristics of printing cylinder:

- 1.1. Diameter : 1.000 mm (39,37").
- 1.2. Width : 2.200 mm (86,61")
- 1.3. Working Width: 2.000 mm (78,74").

2. Heating system and temperature control:

- 2.1. The cylinder is heated by three resistors (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.a system.
- 2.2. The temperature of the cylinder is set by touch screen and regulated by an electronic card. The temperature control is equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).

3. Tension controls:

- 3.1. Tension control for printing material in roll:
 - Entry: disk brake with pneumatic adjustment
 - Exit: independent motor, adjustable by potentiometer
- 3.2. Tension control for printing paper in roll:
 - Entry: disk brake with pneumatic adjustment
 - Exit: special motor with automatic constant tension, adjustable by potentiometer
- 3.3. Tension control for protection paper:
 - Entry: disk brake with pneumatic adjustment
 - Exit: special motor with automatic constant tension, adjustable by potentiometer

4. Other devices into machine:

- 4.1. Long front working table complete with: lateral placement laser
- 4.2. glass plane with placement light
- 4.3. Conveyor-belt for automatic unloading on the back of the machine
- 4.4. Pre-feeder for printing paper, protection paper and textile

All data and technical features are purely indicative and subjected to changes without prior notice



INNOVATION
SPEED
FLEXIBILITY
PROJECT&DESIGN
INSTALLATION AND ASSISTANCE

Monti Antonio S.p.A.
Head Office: via dell'Elettronica n°5, 36016 Thiene (VI) Italy
Operation and Administration: viale della Fisica n°6, 36016 Thiene (VI) Italy
T. +39 0445 364619 - F. +39 0445 364033
sales@montiantonio.com - www.montiantonio.com

MODEL 97



- 4.5. Independent motors with a electronic synchronization system
- 4.6. NOMEX felt with tension adjustment system and automatic felt-centering device
- 4.7. Incorporated system of felt protection in case of black out and/or compressed air lack
- 4.8. Front touch-screen keyboard for production data access and programming

5. Technical data:

- 5.1. Installed power: 75 kw
- 5.2. Average electric consumption: 48 kw/h
- 5.3. Compressed air pressure: 6-8 bar
- 5.4. Mechanic speed: 1 - 15 m/min
- 5.5. Overall dimensions (with pre-feeder): width 4.860 mm (191,33"). length 7.150 mm (281,49"). height 2.960 mm (116,53").
- 5.6. Net weight: 8.165 kg
- 5.7. Machine produced according to CE rules
- 5.8. Customs tariff: 84 51 80 30

All data and technical features are purely indicative and subjected to changes without prior notice



INNOVATION
SPEED
FLEXIBILITY
PROJECT&DESIGN
INSTALLATION AND ASSISTANCE

Monti Antonio S.p.A.
Head Office: via dell'Elettronica n°5, 36016 Thiene (VI) Italy
Operation and Administration: viale della Fisica n°6, 36016 Thiene (VI) Italy
T. +39 0445 364619 - F. +39 0445 364033
sales@montiantonio.com - www.montiantonio.com